

## DL LUBE

### **Description:**

DL is a lubricant that reduces the friction of the clay bar, preventing damage to the surface and removing contamination from paint and glass surfaces. With its special formula, it can also be used with cloths or discs that require lubrication, making the preparation of the vehicle much easier and more efficient for any detailed work.

### **Directions for use:**

thoroughly wash the vehicle. Spray DL on the surface. Work on one panel at a time by sliding the clay bar on the lubricated surface. Once the panel has been treated, dry with a clean microfibre cloth.

### **Consumption:**

20 ml/car

### **Technical Features:**

Appearance and colour: slightly amber liquid

Odour: characteristic

pH: 8,0 ± 0,5

Flash point: >100°C

Relative density: 1,00 g/cm<sup>3</sup>

Solubility in water: soluble

Solubility in oil: not soluble

### **Storage:**

Unopened and stored at room temperature away from direct sunlight.

### **Packaging:**

<b>PACKAGING</b>	<b>BOX</b>	<b>ITEM CODE</b>
500 ml	6 PCS	79288

*FRA-BER s.r.l.  
Head of the laboratory*

*Original signed document available at the company's headquarters. The data contained is the result of technological research of our laboratory and is provided for information purposes only. We exclude any liability arising from an incorrect choice of product and the lack of the necessary precautions, which must always be verified by the user.*